winterhalter®

Item No	:	Qty	:
Electrical	:	Volt	:
Options	:		
Drico			

PASSTHROUGH DISHWASHER



Features:

Integrated control functions

PT-500 has numerous control functions which further reduces staff workload. Tank and boiler temperatures can be shown on the display at any time. Simple symbols warn the personnel when there is a lack of detergent and rinse aid.

A leak sensor monitors uncontrolled water outflows and shuts off the machine's water inlet.

Thus PT-500 guarantees process reliability and prevents resulting damage.

► Time-saving hygiene concept

A deep-drawn tank, a hygiene tank heater and a hygiene rear panel prevent limescale and dirt deposits. These components guarantee that the interior of the machine is clean at all times. In addition, the self-cleaning programme considerably reduces kitchen staff workload.

► Extremely easy to use

To ensure untrained, frequently changing staff can learn to use the machine quickly, PT-500 has a colour coded display showing the various Machine states; heating, washing and standby. Selected washing programmes are also started using the single-button control or automatic hood start. The unique, ergonomic hood handles support effortless operation of the machine especially on long working days.

Model : PT-500

Specifications:

Number of Program	:	3
Capacity / Hour	:	68-20 Racks / 1 Hour (short / standard / intensive programme*)
Capacity Tank	:	62-66 Liter
Tank temperature	:	85 Degree
Machine Dimension wxdxh	:	64 x 75 x 150 cm
Rack dimensions	:	50 x 50 cm
Weight	:	103-128 Kg

^{*} Continuing research results in steady improvements; therefore, these specifications are subject to change without prior notice.



PT MULTI FLASHINDO KARISMA

Jakarta

Jl. Hayam wuruk 114 Blok A No. 4 Jakarta - Indonesia 11160 Telp. (021) 626 8758, Fax. (021) 625 8473

Surabaya :

Jl. Sarono Jiwo No.4 Surabaya - Indonesia 60299 Telp. (031) 847 1460, Fax. (031) 847 1474

Service Center :

Jl. Kamal Raya No.9 RT01/06, Tegal Alur - Cengkareng Telp. (021) 5595 2523/ 2952 8135 Fax. (021) 5595 7271

Email: service.center@mfk.co.id







MFK Channel














winterhalter®

Dimensions







900 mm working height also available instead of 850 mm. That increases the vertical dimensions by 50 mm.



PT MULTI FLASHINDO KARISMA

Jakarta

Jl. Hayam wuruk 114 Blok A No. 4 Jakarta - Indonesia 11160 Telp. (021) 626 8758, Fax. (021) 625 8473

Surabaya :

Jl. Sarono Jiwo No.4 Surabaya - Indonesia 60299 Telp. (031) 847 1460, Fax. (031) 847 1474

Service Center :

Jl. Kamal Raya No.9 RT01/06, Tegal Alur - Cengkareng Telp. (021) 5595 2523/ 2952 8135 Fax. (021) 5595 7271

Email: service.center@mfk.co.id



sales.dept@mfk.co.id

















winterhalter®

Technical data PT 500

Number of programmes

Theoretical capacity (short / standard / intensive programme) : 68 / 30 / 20 [racks / h]

Water consumption

Tank capacity [I] : 35

Rinse water consumption per cycle [I] 2, 4 / 2, 4 / 3, 8

Temperatures

Tank temperature [°C] :62 / 62 / 66

Rinse temperature [°C] :85

Dimensions

Width [mm] : 635 : 750 Depth [mm] Height with hood closed [mm] : 1.485 Height with hood open [mm] : 1.965 Working height [mm] : 850 Clear entry height [mm] : 440

Rack dimensions [mm] : 500 x 500

Electrical specifications

Total connected load

- Three-phase AC [kW] : Differs by country and fuse protection, see below - Alternating current [kW] : Differs by country and fuse protection, see below Fuse protection [A] : Differs by country and fuse protection, see below

Circulating pump (P1) [kW] : 0, 75

Tank heating [kW] : 2, 5 Boiler heating

- Three-phase AC [kW] : Differs by country and fuse protection, see below - Alternating current [kW] : Differs by country and fuse protection, see below

Other information

Max. water inlet temperature [°C] Required water flow pressure [bar / kPA] : 1,0 - 6,0 / 100 - 600

: IP X5 Splash guard

Weight, net / gross [kg] : 103 / 128



PT MULTI FLASHINDO KARISMA

Jl. Hayam wuruk 114 Blok A No. 4 Jakarta - Indonesia 11160 Telp. (021) 626 8758, Fax. (021) 625 8473

Surabaya:

Jl. Sarono Jiwo No.4 Surabaya - Indonesia 60299 Telp. (031) 847 1460, Fax. (031) 847 1474

Service Center:

Jl. Kamal Raya No.9 RT01/06, Tegal Alur - Cengkareng Telp. (021) 5595 2523/ 2952 8135 Fax. (021) 5595 7271

Email: service.center@mfk.co.id



sales.dept@mfk.co.id





MFK Channel











