

Item No	:	Qty	:
Electrical	:	Volt	:
Options	:		
Price	:		

STR Single-Tank Rack Conveyor Dishwashers

Features:

The STR series provides optimum cleaning results achieved through the intelligent interaction of perfected warewashing technology.



- ▶ **High performance warewashing system**
Top quality cleaning results are guaranteed by the perfectly coordinated combination of a powerful pump, five upper and three lower wash arms, optimal water distribution and jets positioned for total coverage.
- ▶ **Pre-wash zone – extra cleaning power**
The pre-wash zone of the STR 200 / STR 260 removes coarse food residue from dishes, which is then captured in an easily removable filter cassette. This reduces the dirt entering the main wash zone.
- ▶ **Wash water filtration**
Large dirt particles are trapped by a removable strainer and pump inlet filter. The Mediamat uses centrifugal force to permanently remove fine impurities, such as coffee grounds, from the wash water.
- ▶ **Gentle glass washing**
With optional temperature switching, the rinse temperature can be reduced to 65 °C. This ensures the gentle washing of glasses.

Model : STR 155

Specifications :

Number of Program	:	Custom
Capacity / Hour	:	155 / 208 racks/h
Capacity Tank	:	62 - 66 Liter
Voltage / Watts	:	AC 380 / 400 3N / 36,7 kW
Tank temperature	:	55 – 65 Degree
Machine Dimension wxdxh	:	130 x 80 x 148 cm
Rack Dimension	:	50 x 50 cm
Weight	:	200-240 Kg

* Continuing research results in steady improvements; therefore, these specifications are subject to change without prior notice.



PT MULTI FLASHINDO KARISMA

Jakarta

Jl. Hayam wuruk 114 Blok A No. 4
Jakarta - Indonesia 11160
Telp. (021) 626 8758,
Fax. (021) 625 8473


Surabaya :

Jl. Saronu Jiwo No.4
Surabaya - Indonesia 60299
Telp. (031) 847 1460,
Fax. (031) 847 1474

Service Center :

Jl. Kamal Raya No.9 RT01/06, Tegal Alur - Cengkareng
Telp. (021) 5595 2523/ 2952 8135
Fax. (021) 5595 7271
Email: service.center@mfk.co.id

STR 155 / STR 208 single-tank rack conveyor dishwasher



Hotel, restaurant, commercial catering with 200–400 diners


Performance: Up to 155/208 racks/h


Total length/depth: 3.700 mm/815 mm

Loading area: Inlet table with sink and pre-spray unit, space for two racks

Removal area: Removal roller conveyor, space for two racks

Model : STR 155





Model	:STR 155
Theoretical capacity [racks/h]	: 100 / 155
Length [mm]	: 1.300
Depth with door closed [mm]	: 800
Depth with door open [mm]	: 1.472
Height without exhaust air vent [mm]	: 1.420
Height with exhaust air vent	: 1.600 (outlet area) [mm]
Height with Energy [mm]	: 1.890
Working height [mm]	: 900
Clear entry height [mm]	: 460
Passage width [mm]	: 500
Circulating pump [kW]	: 1,7 2,0
Tank temperature [°C]	: 55 – 65
Boiler temperature [°C]	: 85 85
Rinse water consumption (full load	: 260)* [l/h]
Minimal water inlet temperature [°C]	: 10
Total connected load	: 36,7 [kW] (with minimal water inlet temperature) [kW]

Optional features

- Energy exhaust air heat recovery
- Direction of travel freely selectable: left – right / right – left
- Working height: 850 mm
- Plinth installation
- Temperature switching for glass washing 85 °C / 65 °C
- Drying zone (Length: 700 mm)
- Infeed tunnel with integrated exhaust air vents (only when equipped with drying zone)
- Outlet tunnel with exhaust air vents (not in combination with drying zone)
- Emergency switch
- Steam-heating (0,3 – 4,0 bar)
- HighTemp (in both programmes only possible with reduced speeds)
- Rinse booster pump to compensate for one-site fluctuations in water pressure (standard feature in some countries)



PT MULTI FLASHINDO KARISMA

Jakarta

Jl. Hayam wuruk 114 Blok A No. 4
 Jakarta - Indonesia 11160
 Telp. (021) 626 8758,
 Fax. (021) 625 8473

Surabaya :

Jl. Sarono Jiwo No.4
 Surabaya - Indonesia 60299
 Telp. (031) 847 1460,
 Fax. (031) 847 1474

Service Center :

Jl. Kamal Raya No.9 RT01/06, Tegal Alur - Cengkareng
 Telp. (021) 5595 2523/ 2952 8135
 Fax. (021) 5595 7271
 Email: service.center@mfk.co.id