



DISINFECT




SMART VOICE

DISINFECTION CABINET

Features

- High quality stainless steel plate
- The integral stretching bottom, clean and sanitary
- Use high-quality and efficient insulation cotton
- Dual temperature sensor, more secure in use
- Deep and shallow basket design, storage more freely
- Intelligent voice controller, powerful function, simple operation
- 360° hot air circulation, sterilizing more thoroughly.
- Two stars disinfection standard



RTD360MC-17



RTD720MC-18

Model		RTD360MC-17	RTD720MC-18
Dimension			
Width	[mm]	650	1310
Depth	[mm]	690	690
Height	[mm]	1980	1980
Capacity	[L]	360	720
Voltage	[V]	220	220
Frequency	[Hz]	50	50
Rated Power	[kW]	2.2	4.4
Temperature Range	[°C]	20~150	20~150
Net Weight	[kg]	95	150
Shelf Bearing	[kg/Layer]	25	25




RTD

INTELLIGENT HOT AIR DISINFECTION CABINT



Features

- High quality stainless steel plate
- The integral stretching bottom, cleaned sanitary.
- Dual temperature sensor, more secure in use.
- Deep and shallow basket design, storage more freely.
- Intelligent control panel, one-click operation, convenient and fast large field of view can be viewed, disinfection can be seen.
- 360°hot air circulation + infrared double sterilization.



Model		RTD360GBR-3	RTD720GBR-4
Dimensions	[mm]	650*720*1980	1310*720*1980
Voltage/ Frequency		220V/50HZ	220V/50HZ
Rated Power	[kW]	2.4	4.8
Capacity	[L]	360	720
Temperature range	[C]	60-125	60-125
Net Weight	[kg]	90	148
Shelf Bearing	[kg/layer]	15	15



merchu.

Commercial Kitchen Equipment

COMBINATION DISINFECTION CABINET



COMBINATION DISINFECTION CABINET



Features

- High quality stainless steel plate
- Intelligent control system, independent operation of upper and lower
- Ozone + ultraviolet + far infrared + 360°hot air circulation, sterilization more thoroughly
- Double toughened glass door body, improve the insulation effect
- Full open glass door for lower which enlarge storage space
- Multi-function storage, lower for chopping board and cutting tools, upper for towel and tools
- Dual temperature sensor, more secure in use




Model		ZTD560MC-1500
Dimension		
Width	[mm]	1500
Depth	[mm]	800
Height	[mm]	800+1180
Capacity	[L]	230+330
Voltage	[V]	220
Frequency	[Hz]	50
Rated Power	[kW]	0.4+1.6
Temperature Range	[°C]	45 / 80
Net Weight	[kg]	175
Shelf Bearing	[kg/Layer]	15



YH-DBW

BANQUET WARMER



Features

- High quality stainless steel plate
- Use high-quality and efficient insulation cotton
- The integral stretching bottom, clean and sanitary
- Convection air supply and heating, heating up fast, the heat preservation temperature is constant and uniform
- The temperature is accurate and adjustable to adapt to different foods
- Electric heating produces moisture, which keeps food moist and tasty during the heat preservation process
- With automatic protection function, double safety of food and equipment

Model		YH-DBW-1	YH-DBW-2
Dimensions	[mm]	730*950*1860	1400*950*1860
Capacity	[L]	510	1100
Voltage/ Frequency		220V/50HZ	220V/50HZ
Rated Power	[kW]	1.8	2.6
Temperature Range	[°C]	20-85 °C	20-85 °C
Net Weight	[kg]	120	210
Tray		11	22
Shelf Bearing	[kg/layer]	15	15

YHO-DBW

SMART CONTROL BANQUET WARMER

Features

Smart touch panel, LCD display, real-time detection and adjustment of the temperature inside the box, ensuring that the food is always within the ideal insulation range.

The door adopts a groove design, with a more novel appearance

There is a drainage structure at the bottom of the inner box, which is more convenient to clean

Adopts convection air supply and heating mode, fast heating, constant and uniform insulation temperature, electric heating to generate moisture, heat preservation and moisture retention 11-layer shelf, which can be adjusted up and down according to the height of the food

The bottom is equipped with an alloy anti-collision to prevent the cabinet from bumping



Model		YHO-DBW-3	YHO-DBW-4
Dimensions	[mm]	790*950*1860	1500*950*1860
Voltage/ Frequency		220V/50HZ	220V/50HZ
Rated Power	[kW]	1.8	2.6
Capacity	[L]	510	1130
Temperature Range	[℃]	20-85℃	20-85℃
Tray	[pcs]	11	22
Shelf Bearing	[kg/layer]	15	15



WARMER SHOWCASE



Features

- High quality stainless steel plate
- Cyclopentane insulation foaming agent
- The integral stretching bottom, clean and sanitary
- Dual temperature sensor, more secure in use
- Front and back slide door, easy to open and close
- Black crystal panel, beautiful appearance



Model		RTP930MC-1
Dimension		
Width	[mm]	1400
Depth	[mm]	630
Height	[mm]	2030
Capacity	[L]	930
Voltage	[V]	220
Frequency	[Hz]	50
Rated Power	[kW]	2.4
Temperature Range	[°C]	20~90
Net Weight	[kg]	175
Shelf Bearing	[kg/Layer]	25



WARMER SHOWCASE

Features

- High quality stainless steel plate.
- Toughened glass door top open type design, easy to open and save space.
- Back toughened glass.
- Intelligent control system, can be adjusted according to the demand.
- Equipped with warm light lamp.
- With a small adjusting foot, can be put on the table.
- Hot air circulation .



Model		RTD160MC-T1
Dimension		
Width	[mm]	1200
Depth	[mm]	430
Height	[mm]	680
Capacity	[L]	160
Voltage	[V]	220
Frequency	[Hz]	50
Rated Power	[kW]	1.5
Temperature Range	[°C]	20~80
Net Weight	[kg]	65
Shelf Bearing	[kg/Layer]	25

Features

- High quality stainless steel plate.
- Toughened pass-through glass door top open type design, easy to open and save space.
- Front and rear glass.
- With a small adjusting foot, can be put on the table.
- Hot air circulation.



Model		RTD330MC-T2
Dimension		
Width	[mm]	1200
Depth	[mm]	680
Height	[mm]	1200
Capacity	[L]	330
Voltage	[V]	220
Frequency	[Hz]	50
Rated Power	[kW]	1.5
Temperature Range	[°C]	20~80
Net Weight	[kg]	70
Shelf Bearing	[kg/Layer]	25



WALL-MOUNTED DISINFECTION CABINET



RGP150MC-1



RGP150MC-2

Features

- High quality stainless steel plate
- Use high-quality and efficient insulation cotton
- Independent water tray design
- Dual temperature sensor, more secure in use
- Can be wall hanging, can be put on the table, save space



Low Temp.
Disinfection



PICC
Insured
Product



Glass Window

Model		RGP150MC-1	RGP150MC-2
Dimension			
Width	[mm]	1230	1230
Depth	[mm]	440	450
Height	[mm]	700	700
Capacity	[L]	150	150
Voltage	[V]	220	220
Frequency	[Hz]	50	50
Rated Power	[kW]	1.3	1.3
Temperature Range	[°C]	20~90	20~90
Net Weight	[kg]	50	50
Shelf Bearing	[kg/Layer]	15	15



SHOWCASE

BAKING

FOOD MACHINERY

STEAMING CABINET

DISINFECTION

DISHWASHERS

REFRIGERATION



PT MULTI FLASHINDO KARISMA

□ JAKARTA

Jl. Hayam Wuruk 114 Blok A No.4,
Maphar. Jakarta - Indonesia 11160
Phone: +62 21 626 8758
Whatsapp: +62 811 1210 6803
Email: sales.dept@mfk.co.id

□ SURABAYA

Ruko Royal Crown Palace RA 2
Jl. H. Anwar Hamzah, Kp. Baru, Tambakoso,
Kec. Waru, Kab. Sidoarjo, Jawa Timur 61256
Phone: +62 31 3592 9091
Whatsapp: +62 811 1210 6803
Email: sales.sby@mfk.co.id

□ BALI

Jl. Sunset Road No.108b, Kec. Kuta
Kab. Badung, Bali - Indonesia 80361
Phone: +62 361 934 2633
Whatsapp: +62 811 1210 6803
Email: sales.bali@mfk.co.id

□ SERVICE CENTER

Jl. Kamal raya No.9 Unit G, RT 01/RW 06
Tegal Alur. Cengkareng - Indonesia 11820
Phone: +62 21 5595 2523
Whatsapp: +62 811 9144 614
Email: service.center@mfk.co.id