

CAUTION  
MAX HOT FILL LINE



STANDBY

RPM  
**18500**

START/STOP

HEAVY DUTY  
VARIABLE  
SPEED BLENDER

MIN MAX

WARING

WARING COMMERCIAL XTREME

WARING

1 2 3 4

+

SPEED

-

ON/OFF

START STOP

MAX

PULSE

NORM

WARING ON I OFF O

**WARING**  
LABORATORY SCIENCE

# HISTORY

When Fred Waring presented his Miracle Mixer to consumers at the 1937 National Restaurant Show in Chicago, he could not have imagined that one day a Waring® blender would play a part in altering history.

Years before antibiotics were in common use, Waring was asked to produce a sealed, stainless steel container for scientific labs – and Waring Laboratory Science was born.

In the early 1950s, Dr. Jonas Salk used a Waring® blender with an aseptic dispersal container to develop his lifesaving polio vaccine.

Today, Waring remains one of the most respected names in the clinical laboratory industry, providing researchers with the tools they need to move science forward.



# TABLE OF CONTENTS

**1 & 1.2-Liter Blenders ..... 4**

**TBB Series Blenders ..... 12**

**MX Series Blenders ..... 15**

**4-Liter Blenders ..... 19**

**Hazardous Location Blenders ..... 22**

**Immersion Blenders ..... 24**

**Laboratory Processors ..... 27**

**Ice Crusher ..... 31**

**Laboratory Mixers ..... 32**

**Planetary Mixers ..... 33**

**Laboratory Accessories ..... 37**



## 700G / 800G SERIES

### Features:

- One-speed, toggle-switch operation
- Base: die-cast, epoxy-coated motor housing
- 1.2-liter, heat-resistant glass container with handle and two-piece vinyl and styrene lid
- .5 HP motor

SKU	Technical Info	Approvals	Plug
700G	120V, 60 Hz	cTUVus	B ☺
800G	230V, 50 Hz	RoHS	F ☺
800EG	230V, 50 Hz	CE, RoHS	F ☺
800EGK	230V, 50 Hz	CE, RoHS	G ☺

*For additional models, see page 23.*



## 700S / 800S SERIES

### Features:

- One-speed, toggle-switch operation
- Base: die-cast, epoxy-coated motor housing
- 1 liter, stainless steel container with handle and two-piece vinyl and styrene lid
- .5 HP motor

SKU	Technical Info	Approvals	Plug
700S	120V, 60 Hz	cTUVus	B ☺
800S	230V, 50 Hz	RoHS	F ☺
800ES	230V, 50 Hz	CE, RoHS	F ☺
800ESK	230V, 50 Hz	CE, RoHS	G ☺

*For additional models, see page 23.*



## 7011G / 8011G SERIES

### Features:

- Two-speed, push-button operation
- Base: die-cast, epoxy-coated motor housing
- 1.2-liter, heat-resistant glass container with handle and two-piece vinyl and styrene lid
- .5 HP motor

SKU	Technical Info	Approvals	Plug
7011G	120V, 60 Hz	cTUVus	B ☺
8011G	230V, 50 Hz	RoHS	F ☺
8011EG	230V, 50 Hz	CE, RoHS	F ☺
8011EGK	230V, 50 Hz	CE, RoHS	G ☺

*For additional models, see page 23.*



## 7011S / 8011S SERIES

### Features:

- Two-speed, push-button operation
- Base: die-cast, epoxy-coated motor housing
- 1 liter, stainless steel container with handle and two-piece vinyl and styrene lid
- .5 HP motor

SKU	Technical Info	Approvals	Plug
7011S	120V, 60 Hz	cTUVus	B ☺
8011S	230V, 50 Hz	RoHS	F ☺
8011ES	230V, 50 Hz	CE, RoHS	F ☺
8011ESK	230V, 50 Hz	CE, RoHS	G ☺

*For additional models, see page 23.*



## 7010G / 8010G SERIES

### Features:

- Two-speed, push-button operation
- Base: die-cast, epoxy-coated motor housing
- 1.2-liter, heat-resistant glass container with handle and two-piece vinyl and styrene lid
- Mechanical timer
- .5 HP motor

SKU	Technical Info	Approvals	Plug
7010G	120V, 60 Hz	cTUVus	B ☺
8010G	230V, 50 Hz	RoHS	F ☹
8010EG	230V, 50 Hz	CE, RoHS	F ☹
8010EGK	230V, 50 Hz	CE, RoHS	G ☹

*For additional models, see page 23.*



## 7010S / 8010S SERIES

### Features:

- Two-speed, push-button operation
- Base: die-cast, epoxy-coated motor housing
- 1 liter, stainless steel container with handle and two-piece vinyl and styrene lid
- Mechanical timer
- .5 HP motor

SKU	Technical Info	Approvals	Plug
7010S	120V, 60 Hz	cTUVus	B ☺
8010S	230V, 50 Hz	RoHS	F ☺
8010ES	230V, 50 Hz	CE, RoHS	F ☺
8010ESK	230V, 50 Hz	CE, RoHS	G ☺

*For additional models, see page 23.*

# LABORATORY BLENDERS

## 1 & 1.2 LITER BLENDERS



## LB10XG / LB20XS SERIES

### Features:

- Variable-speed with dial and On/Off toggle switch
- RPM display for added versatility and consistency control
- Base: die-cast, epoxy-coated motor housing 1 HP motor
- 1.2-liter, heat-resistant glass container with handle and two-piece vinyl and styrene lid

SKU	Technical Info	Approvals	Plug
LB10XG	120V, 50-60 Hz	cTUVus	B ☺
LB20XEG	230V, 50 Hz	CE, RoHS	F ☺



## LB10XS / LB20XS SERIES

### Features:

- Variable-speed with dial and On/Off toggle switch
- RPM display for added versatility and consistency control
- Base: die-cast, epoxy-coated motor housing 1 HP motor
- 1.2-liter, stainless steel container with handle and two-piece vinyl and styrene lid

SKU	Technical Info	Approvals	Plug
LB10XS	220V-240V, 50-60 Hz	cTUVus	B ☺
LB20XES	220V-240V, 50-60 Hz	CE, RoHS	F ☺



## TBB145 SERIES

### Features:

- HI, LO, OFF and PULSE toggle switches
- High performance, 2 HP motor
- 1.4-liter copolyester container
- Durable stainless steel drive coupling
- Also available with stainless steel containers

SKU	Technical Info	Approvals	Plug
TBB145	120V, 60 Hz	cETL, NSF	B ☺
TBB145E	230V, 50 Hz	CE, RoHS	F ☺
TBB145K	230V, 50 Hz	CE, RoHS	G ☺

*For additional models, see page 23.*



## TBB160 SERIES

### Features:

- Electronic membrane keypad with 60-second countdown timer
- High performance, 2 HP motor
- 1.4-liter copolyester container
- Durable stainless steel drive coupling
- Also available with stainless steel containers

SKU	Technical Info	Approvals	Plug
TBB160	120V, 60 Hz	cETL, NSF	B ☺
TBB160E	230V, 50 Hz	CE, RoHS	F ☺
TBB160K	230V, 50 Hz	CE, RoHS	G ☺

*For additional models, see page 23.*



## TBB175 SERIES

### Features:

- Variable-speed control dial operates from 1,000 to 17,000 RPM
- PULSE feature overrides speed 10 at 24,000 RPM
- High performance, 2 HP motor
- 1.4-liter copolyester container
- Durable stainless steel drive coupling
- Also available with stainless steel containers

SKU	Technical Info	Approvals	Plug
TBB175	120V, 60 Hz	cETLus, NSF	B ☹
TBB175E	230V, 50 Hz	CE, RoHS	F ☹
TBB175K	230V, 50 Hz	CE, RoHS	G ☹

*For additional models, see page 23.*



## MX1000XTX SERIES

### Features:

- HI, LO, OFF and PULSE paddle switches
- Heavy-duty base with powerful, 3.5 peak input HP motor
- One-piece, dishwasher-safe, removable jar pad
- 2-liter, BPA-free, copolyester container
- Durable stainless steel drive coupling
- Also available with stainless steel containers

SKU	Technical Info	Approvals	Plug
MX1000XTX	120V, 60 Hz	cETLus, NSF	B
MX1000XTXEE	230V, 50 Hz	CE, RoHS	F
MX1000XTXEK	230V, 50 Hz	CE, RoHS	G

*For additional models, see page 23.*



## MX1100XTX SERIES

### Features:

- Easy-to-clean electronic membrane keypad with STOP, HI, LO, and PULSE controls
- 30-second electronic countdown timer
- Heavy-duty base with powerful, 3.5 peak input HP motor
- One-piece, dishwasher-safe, removable jar pad
- 2-liter, BPA-free, copolyester container
- Durable stainless steel drive coupling
- Also available with stainless steel containers

SKU	Technical Info	Approvals	Plug
MX1100XTX	120V, 60 Hz	cETLus, NSF	B ☺
MX1100XTXEE	230V, 50 Hz	CE, RoHS	F ☺
MX1100XTXEK	230V, 50 Hz	CE, RoHS	G ☺

*For additional models, see page 23.*

## MX1200TX SERIES

### Features:

- Variable-speed control dial operates from 1,500 to 24,000 RPM
- PULSE feature overrides speed 10 at 30,000+ RPM
- Heavy-duty base with powerful, 3.5 peak input HP motor
- One-piece, dishwasher-safe, removable jar pad
- 2-liter, BPA-free, copolyester container
- Durable stainless steel drive coupling
- Also available with stainless steel containers

SKU	Technical Info	Approvals	Plug
MX1200TX	120V, 60 Hz	cETLus, NSF	B ☺
MX1200TXEE	230V, 50 Hz	CE, RoHS	F ☺
MX1200TXEK	230V, 50 Hz	CE, RoHS	G ☺

*For additional models, see page 23.*



*For full list of accessories, see pages 39-41.*



## MX1300XTX SERIES

### Features:

- Electronic membrane keypad with 4 programmable settings and blue backlit LCD display for easy viewing and program selection
- Programmable speed control from 1,500 to 24,000 RPM
- Dual PULSE feature includes PULSE and MAX PULSE, overriding speed 10 at 30,000+ RPM
- Heavy-duty base with powerful, 3.5 peak input HP motor
- One-piece, dishwasher-safe, removable jar pad
- 2-liter, BPA-free, copolyester container
- Durable stainless steel drive coupling
- Also available with stainless steel containers

SKU	Technical Info	Approvals	Plug
MX1300XTX	120V, 60 Hz	cETLus, NSF	B ☺
MX1300TXEE	230V, 50 Hz	CE, RoHS	F ☺
MX1300TXEK	230V, 50 Hz	CE, RoHS	G ☺

*For additional models, see page 23.*



## CB15VX SERIES

### Features:

- Variable speed with RPM display for added versatility and consistency control
- 4-liter, stainless steel container with two handles and two-piece, easy-off, rubberized lid
- Easy-to-clean electronic keypad
- Heavy-duty base with powerful, 3.75 peak input HP motor
- One-piece, dishwasher-safe, removable jar pad

SKU	Technical Info	Approvals	Plug
CB15VX	120V, 60 Hz	cETLus, NSF	B Ⓟ
CB15VXE	230V, 50 Hz	CE, RoHS	F Ⓟ
CB15VXK	230V, 50 Hz	CE, RoHS	G Ⓟ

*For additional models, see page 23.*



## LBC15 SERIES

### Features:

- Easy-to-clean, electronic membrane keypad with 3 speeds plus PULSE
- 4-liter, stainless steel container with two handles and stainless steel lid
- Heavy-duty base with powerful, 3.75 peak input HP motor
- One-piece, dishwasher-safe, removable jar pad

SKU	Technical Info	Approvals	Plug
LBC15	120V, 60 Hz	cETLus, NSF	B Ⓢ
LBC15E	230V, 50 Hz	CE, RoHS	F Ⓢ

*For additional models, see page 23.*



## CB15T SERIES

### Features:

- Easy-to-clean, electronic membrane keypad with 3-minute countdown timer and 3 speeds plus PULSE
- 4-liter, stainless steel container with two handles and two-piece, easy-off, rubberized lid
- Heavy-duty base with powerful, 3.75 peak input HP motor
- One-piece, dishwasher-safe, removable jar pad

SKU	Technical Info	Approvals	Plug
CB15T	120V, 60 Hz	cETLus, NSF	B
CB15TE	230V, 50 Hz	CE, RoHS	F
CB15TK	230V, 50 Hz	CE, RoHS	G

*For additional models, see page 23.*



## BHL120 / BHL240

The standard in safety. Depend on these Waring® blenders to provide optimum safety and reliable performance when working with highly volatile substances.

### Features:

- For use with 1 liter, stainless steel container only (HL515)
- Natural finished aluminum and steel housing
- Cord not included. Must be hard-wired via explosion-proof conduit
- External switch available as an accessory (BHLSW)
- UL listed motor for use in Class 1, Group D hazardous locations

### Hazardous Location Blender Motor

Heat is generated within motor housing during normal operation. This blender is designed to prevent the electrical arcing and generated heat from igniting ambient atmospheres.

SKU	Technical Info	Approvals	Plug
BHL120	120V, 60 Hz	N/A	N/A
BHL240	230V, 50 Hz	RoHS	N/A



# ADDITIONAL MODELS

## One Liter Series – Single Speed

- 700BU Base Only, 120V
- 800BU Base Only, 230V (non CE)\*
- 800EBU Base Only, 230V (CE approved)\*
- 800EKBU Base Only, 230V (CE approved)\*\*

## One Liter Series - Two Speeds

- 7011BU Base Only, 120V
- 7011HB Base Only, Heavy Duty, 120V
- 7011HG Heavy-Duty, Glass Container, 120V
- 7011HS Heavy-Duty, Stainless Container, 120V
- 8011BU Base Only, 230V (non CE)\*
- 8011EB Base Only, 230V (CE approved)\*
- 8011EKB Base Only, 230V (CE approved)\*\*

## One Liter Series, Two Speeds w/ Timer

- 7010BU Base Only, 120V
- 7010HB Base Only, Heavy Duty, 120V
- 7010HG Heavy-Duty, Glass Container, 120V
- 7010HS Heavy-Duty, Stainless Container, 120V
- 8010BU Base Only, 230V (non CE)\*
- 8010EB Base Only, 230V (CE approved)\*
- 8010EKB Base Only, 230V (CE approved)\*\*

## CB15 Series

- CB15BU Base Only, 120V
- CB15EB Base Only, 230V\*

## CB15V Series

- CB15VXP 4-Liter Plastic Jar, 120V
- CB15VXE Base Only, RPM Display, 230V\*
- CB15VXKB Base Only, RPM Display, 230V\*\*

## TBB145 Series

- TBB145S6 2-Liter Stainless Container, 120V
- TBB145S4 1.4-Liter Stainless Container, 120V
- TBB145EB Base Only, 230V\*

## TBB160 Series

- TBB160S6 2-Liter Stainless Container, 120V
- TBB160S4 1.4-Liter Stainless Container, 120V
- TBB160EB Base Only, 230V\*

## TBB175 Series

- TBB175S6 2-Liter Stainless Container, 120V
- TBB175S4 1.4-Liter Stainless Container, 120V
- TBB175EB Base Only, 230V\*

## MX1000 Series

- MX1000XTS 2-Liter Stainless Container, 120V
- MX1000XTEES 2-Liter Stainless Container, 230V\*
- MX1000XTEKS 2-Liter Stainless Container, 230V\*\*

## MX1100 Series



- MX1100XTS 2-Liter Stainless Container, 120V
- MX1100XTEES 2-Liter Stainless Container, 230V\*
- MX1100XTEKS 2-Liter Stainless Container, 230V\*\*

## MX1200 Series

- MX1200XTS 2-Liter Stainless Container, 120V
- MX1200XTEES 2-Liter Stainless Container, 230V\*
- MX1200XTEKS 2-Liter Stainless Container, 230V\*\*

## MX1300 Series

- MX1300XTS 2-Liter Stainless Container, 230V
- MX1300XTEES 2-Liter Stainless Container, 230V\*
- MX1300XTEKS 2-Liter Stainless Container, 230V\*\*

\*F Plug Type  \*\*G Plug Type 



### WSB35

#### Features:

- 2-speed operation
- Stainless steel, 18 cm (7") fixed shaft and blade
- Lightweight and compact
- 3-gallon, 12 quart capacity

SKU	Technical Info	Approvals	Plug
WSB35	120V, 60 Hz	cULus, NSF	5-15P
WSB35E	230V, 50 Hz	CE, RoHS	F
WSB35K	230V, 50 Hz	CE, RoHS	G



## WSB40 SERIES

### Features:

- 2-speed operation
- Rubberized comfort grip
- Stainless steel, 25.5 cm (10") fixed shaft and blade
- 6-gallon, 24 quart capacity

---

SKU	Technical Info	Approvals	Plug
WSB40	120V, 60 Hz	cETLus, NSF	B ☺
WSB40E	230V, 50 Hz	CE, RoHS	F ☻
WSB40K	230V, 50 Hz	CE, RoHS	G ☼

# LABORATORY IMMERSION BLENDERS

## WSB50/WSB60/WSB65/WSB70 SERIES

### HEAVY-DUTY IMMERSION BLENDERS



WSB50



WSB55



WSB60



WSB65



WSB70

### Features:

- Variable-speed motor – 9 settings
- Completely sealed stainless steel shaft is easily removable and dishwasher safe
- Universal power pack fits all shaft sizes
- Rubberized comfort grip and second handle for safe and controlled operation
- Continuous ON feature
- User-replaceable couplings on power pack and shaft
- All-purpose stainless steel blade
- 12-foot cord

SKU	Shaft Length	Technical Info	Approvals	Plug
WSB50	30.5 cm/12"	120V, 60 Hz	cETLus, NSF	B ☺
WSB50CE	30.5 cm/12"	230V, 50 Hz	CE, RoHS	F ☹
WSB55	35.6 cm/14"	120V, 60 Hz	cETLus, NSF	B ☺
WSB55CE	35.6 cm/14"	230V, 50 Hz	CE, RoHS	F ☹
WSB60	40.6 cm/16"	120V, 60 Hz	cETLus, NSF	B ☺
WSB60CE	40.6 cm/16"	230V, 50 Hz	CE, RoHS	F ☹
WSB65	45.7 cm/18"	120V, 60 Hz	cETLus, NSF	B ☺
WSB65CE	45.7 cm/18"	230V, 50 Hz	CE, RoHS	F ☹
WSB70	53.4 cm/21"	120V, 60 Hz	cETLus, NSF	B ☺
WSB70CE	53.4 cm/21"	230V, 50 Hz	CE, RoHS	F ☹



## WCG75 SERIES

### Features:

- .75 HP motor
- Chopping assembly: .7 liter work bowl, 2-blade hub, cover with 2 protected openings for adding ingredients while processing
- Grinding assembly: .7 liter work bowl, 3-blade hub, sealed cover with handle
- Bowl assemblies stack for storage



SKU	Technical Info	Approvals	Plug
WCG75	120V, 60 Hz	ETLus, ETL Sanitation	B ☺
WCG75E	230V, 50 Hz	CE, RoHS	F ☺
WCG75K	230V, 50 Hz	CE, RoHS	G ☺



### WFP14S SERIES

#### Features:

- 1 HP motor
- 3.3-liter, unbreakable, clear-view batch bowl with LiquiLock® Seal System for processing liquids
- Easy ON and OFF/PULSE control paddles
- Extra-large feed tube and pusher

- **Included processing accessories:**
  - Sealed, serrated S-blade (WFP14S1)
  - 2 mm (5/64") slicing disc (WFP145)
  - 4 mm (5/32") shredding disc (WFP144)

SKU	Technical Info	Approvals	Plug
WFP14S	120V, 60 Hz	ULus, ETL Sanitation	B ☺
WFP14SE	230V, 50 Hz	CE, RoHS	F ☺
WFP14SK	230V, 50 Hz	CE, RoHS	G ☺

# LABORATORY PROCESSORS

## WFP16SCD SERIES

### Features:

- 2 HP commercial motor
- Die-cast housing
- ON, OFF and PULSE controls
- 3.75-liter, unbreakable, clear-view batch bowl with LiquiLock® Seal System
- Continuous-feed chute for large-volume processing



### • Included processing accessories:

Sealed S-blade (WFP16S1), sealed and locked whipping disc (WFP16S11), adjustable slicing disc 1–6 mm (WFP16S10), reversible shredding disc (WFP16S12)

SKU	Technical Info	Approvals	Plug
WFP16SCD	120V, 60 Hz	ETLus, ETL Sanitation	B ☺
WFP16SCDE	230V, 50 Hz	CE, RoHS	F ☹
WFP16SCDK	230V, 50 Hz	CE, RoHS	G ☹

3.75-LITER CONTINUOUS FEED PROCESSORS

# LABORATORY PROCESSORS

## 5.7-LITER CONTINUOUS FEED PROCESSOR



### FP2200

#### Features:

- 3.75 HP motor
- Clear, durable Lexan® work bowl holds 3.7 liters wet and 5.7 liters dry ingredients
- Two-handed batch bowl provides safe grip and balance when lifting, pouring, or carrying
- ON, OFF and PULSE controls
- 2-piece S-blade with patented mid-blade minimizes processing time (CAF31)
- Overload safety reset for safe, controlled restarts



- **Included processing accessories:**  
Dual S-blade with patented mid-blade, slicing disc, 3.2 mm (CAF12), shredding disc, 4.7 mm (CAF20)

SKU	Technical Info	Approvals	Plug
FP2200	120V, 60 Hz	cULus, NSF	B ☺

# LABORATORY ICE CRUSHER



## IC20

### Features:

- Container holds more than 2 liters of crushed ice
- Special height adjustment dispenses into 1 liter or 1.4-liter blender containers, as well as a variety of other container sizes
- Large chute and funnel for easy feeding
- Brushed stainless steel exterior

---

SKU	Technical Info	Approvals	Plug
IC20	230V, 50 Hz	CE, RoHS	F

# LABORATORY MIXERS

## WDM120TX SERIES




### Features:

- 1 peak HP motor
- Electronic 3-speed and pulse controls maintain speed under load for optimal performance – 15,000 / 18,000 / 21,000 RPM
- Fully automatic START/STOP operation
  - Motor will run at selected speed once cup is in position
  - Frees up operator for other tasks and ensures consistent results
- Die-cast housing
- Cup slides into position without tilt
- Includes 1 stainless steel cup (CAC20)
- 2- and 3-head models available



SINGLE HEAD MIXERS

---

SKU	Technical Info	Approvals	Plug
WDM120TX	120V, 60 Hz	cETLus, NSF	B 
WDM120TXE	230V, 50 Hz	CE, RoHS	F 
WDM120TXK	230V, 50 Hz	CE, RoHS	G 

# LABORATORY PLANETARY MIXERS

## WSM7L

### Features:

- Large, 7-quart stainless steel bowl with stainless steel handle
- Heavy duty, .5 HP motor
- Front-mounted controls and LED power light
- 11 mixing speeds with variable speed control dial
- Removable, clear-view splash guard with feed chute
- Tilt-back head for easy removal of attachments and cleaning
- Heavy-duty head-lift/release lever
- Gear driven, permanent lube transmission
- Thermal overload protection
- Includes stainless steel bowl, whisk, mixing hook and paddle
- Dishwasher-safe accessories
- Non-slip rubber feet



SKU	Technical Info	Approvals	Plug
WSM7L	120V, 60 Hz	cETLus, NSF	B Ⓢ

7-QUART PLANETARY MIXER

# LABORATORY PLANETARY MIXERS

## 10-QUART PLANETARY MIXER



## WSM10LT

### Features:

- Large, 10-quart stainless steel bowl with stainless steel handle
- Integrated, easy to use 99-minute countdown timer
- Heavy duty, .75 HP induction motor
- Side-mounted controls
- 3 mixing speeds
- Heavy-duty bowl-lift lever
- Gear driven, permanent lube transmission
- Thermal overload protection
- Includes stainless steel bowl, whisk, mixing hook and aluminum paddle
- Specifically designed for countertop use
- Non-slip rubber feet

SKU	Technical Info	Approvals	Plug
WSM10LT	120V, 60 Hz	cETLus, NSF	B ☺

# LABORATORY PLANETARY MIXERS



## WSM20LT

### Features:

- Large, 20-quart stainless steel bowl with stainless steel handle
- Integrated, easy to use 99-minute countdown timer
- Heavy duty, 1 HP induction motor
- Side-mounted controls
- 3 mixing speeds
- Heavy-duty bowl-lift lever
- Gear driven, permanent lube transmission
- Thermal overload protection
- Includes stainless steel bowl, whisk, mixing hook, and aluminum paddle
- Specifically designed for countertop use
- Non-slip rubber feet

SKU	Technical Info	Approvals	Plug
WSM20LT	120V, 60 Hz	cETLus, NSF	B ⚡

20-QUART PLANETARY MIXER











# LABORATORY ACCESSORIES



# LABORATORY ACCESSORIES



For use with all Waring Laboratory Blenders.






	Part Number / Description
	<p><b>CAC32</b> 1.2-liter glass container complete with two-piece lid</p> <p><b>For use with:</b> All 1 liter and 1.2-liter blender bases All 2-liter blender bases with the use of an adapter (AD2) All MX and TBB blender bases with the use of an adapter (AD3) All 4-liter blender bases with the use of an adapter (AD1)</p>
	<p><b>CAC33</b> 1 liter stainless steel container with two-piece lid</p> <p><b>For use with:</b> All 1 liter and 1.2-liter blender bases All 2-liter blender bases with the use of an adapter (AD2) All MX and TBB blender bases with the use of an adapter (AD3) All 4-liter blender bases with the use of an adapter (AD1)</p>
	<p><b>CAC64</b> ½ liter polypropylene container with screw-topped lid</p> <p><b>For use with:</b> All 1 liter and 1.2-liter blender bases All 2-liter blender bases with the use of an adapter (AD2) All MX and TBB blender bases with the use of an adapter (AD3) All 4-liter blender bases with the use of an adapter (AD1)</p>
	<p><b>MC1</b> Stainless steel mini container with lid (12–37 ml capacity)</p> <p><b>For use with:</b> All 1 liter and 1.2-liter blender bases All 2-liter blender bases with the use of an adapter (AD2) All MX and TBB blender bases with the use of an adapter (AD3) All 4-liter blender bases with the use of an adapter (AD1)</p>
	<p><b>MC2</b> Stainless steel mini container with lid (37–110 ml capacity)</p> <p><b>For use with:</b> All 1 liter and 1.2-liter blender bases All 2-liter blender bases with the use of an adapter (AD2) All MX and TBB blender bases with the use of an adapter (AD3) All 4-liter blender bases with the use of an adapter (AD1)</p>
	<p><b>MC3</b> Stainless steel mini container with lid (50–250 ml capacity)</p> <p><b>For use with:</b> All 1 liter and 1.2-liter blender bases All 2-liter blender bases with the use of an adapter (AD2) All MX and TBB blender bases with the use of an adapter (AD3) All 4-liter blender bases with the use of an adapter (AD1)</p>

	Part Number / Description
	<p><b>SS110</b> Dry blending stainless steel container with lid (10–75 grams dry capacity)</p> <p><b>For use with:</b> All 1 liter and 1.2-liter blender bases All 2-liter blender bases with the use of an adapter (AD2) All MX and TBB blender bases with the use of an adapter (AD3) All 4-liter blender bases with the use of an adapter (AD1)</p>
	<p><b>SS115</b> Dry blending, stainless steel container with lid (500 ml capacity)</p> <p><b>For use with:</b> All 1 liter and 1.2-liter blender bases All 2-liter blender bases with the use of an adapter (AD2) All MX and TBB blender bases with the use of an adapter (AD3) All 4-liter blender bases with the use of an adapter (AD1)</p>
	<p><b>SS510C</b> 1 liter stainless steel cool base container</p> <p><b>For use with:</b> All 1 liter and 1.2-liter blender bases All 2-liter blender bases with the use of an adapter (AD2) All MX and TBB blender bases with the use of an adapter (AD3) All 4-liter blender bases with the use of an adapter (AD1)</p>
	<p><b>SS515</b> 1 liter stainless steel container with stainless steel lid and Teflon® gaskets</p> <p><b>For use with:</b> All 1 liter and 1.2-liter blender bases All 2-liter blender bases with the use of an adapter (AD2) All MX and TBB blender bases with the use of an adapter (AD3) All 4-liter blender bases with the use of an adapter (AD1)</p>
	<p><b>SS510F</b> Stainless steel foam arrester</p> <p><b>For use with:</b> SS510C and SS515 containers</p>
	<p><b>SS510S</b> 1 liter stainless steel container with sealed cover</p> <p><b>For use with:</b> All 1 liter and 1.2-liter blender bases All 2-liter blender bases with the use of an adapter (AD2) All MX and TBB blender bases with the use of an adapter (AD3) All 4-liter blender bases with the use of an adapter (AD1)</p>



# LABORATORY ACCESSORIES



## For use with all Waring Laboratory Blenders.

	Part Number / Description
	<p><b>SS510T</b> Stainless steel temperature control coil</p> <p><b>For use with:</b> SS510C and SS515 containers</p>
	<p><b>SS610</b> 1 liter stainless steel container with stainless steel lid</p> <p><b>For use with:</b> All 1 liter and 1.2-liter blender bases All 2-liter blender bases with the use of an adapter (AD2) All MX and TBB blender bases with the use of an adapter (AD3) All 4-liter blender bases with the use of an adapter (AD1)</p>
	<p><b>SS610F</b> Stainless steel foam arrester</p> <p><b>For use with:</b> SS610 and CAC33 containers</p>
	<p><b>SS610T</b> Stainless steel temperature control coil</p> <p><b>For use with:</b> SS610 and CAC33 containers</p>

	Part Number / Description
	<p><b>LA1</b> Variable speed control</p> <p><b>For use with:</b> 120V blenders up to 10 amp</p>
	<p><b>CAT1</b> Digital 1 second to 60-minute timer</p> <p><b>For use with:</b> 120V blenders</p>
	<p><b>CAC24</b> External digital tachometer</p> <p><b>For use with:</b> 7009G 7009S</p>
	<p><b>HL515</b> 1 liter stainless steel container with stainless steel lid and Teflon® seals</p> <p><b>For use with:</b> BHL120 BHL240</p>
	<p><b>BHLSW</b> Hazardous location rated switch</p> <p><b>For use with:</b> BHL120, BHL240</p>




## For use with TBB Series Blenders.



	Part Number / Description
	<p><b>CAC139</b> 1.4-liter, BPA-free, copolyester container with blade and assembly</p> <p><b>For use with:</b> TBB series blender bases only</p>
	<p><b>CAC152</b> 1.4-liter, stainless steel container with two-piece lid</p> <p><b>For use with:</b> TBB series blender bases only</p>

	Part Number / Description
	<p><b>CAC90I</b> 2-liter, stainless steel container with two-piece lid</p> <p><b>For use with:</b> TBB and MX series blender bases only</p>
	<p><b>AD3</b> Adapter for MX and TBB series blenders. Allows the use of 1.2-liter and smaller containers</p> <p><b>For use with:</b> TBB and MX series blender bases only</p>




# LABORATORY ACCESSORIES

## For use with MX Series Blenders.

	Part Number / Description
	<p><b>CAC93XI</b> 1.4-liter, BPA-free, copolyester container with blade and assembly</p> <p><b>For use with:</b> MX series blender bases only</p>
	<p><b>CAC95I</b> 2-liter, BPA-free, copolyester container with two-piece lid</p> <p><b>For use with:</b> MX series blender bases only</p>
	<p><b>CAC90I</b> 2-liter, stainless steel container with two-piece lid</p> <p><b>For use with:</b> MX and TBB series blender bases only</p>

	Part Number / Description
	<p><b>SE1500</b> Sound enclosure for MX series blenders.</p> <p><b>For use with:</b> MX series blender bases only</p>
	<p><b>AD3</b> Adapter for MX and TBB series blenders. Allows the use of 1.2-liter and smaller containers</p> <p><b>For use with:</b> MX and TBB series blender bases only</p>




## For use with 4-Liter Blenders.



	Part Number / Description
	<p><b>CAC70</b> 4-liter, stainless steel container with stainless steel lid</p> <p><b>For use with:</b> 4-liter blender bases only</p>
	<p><b>CAC72</b> 4-liter, stainless steel container with two-piece lid</p> <p><b>For use with:</b> 4-liter blender bases only</p>
	<p><b>2610C</b> Stainless steel, cool base container</p> <p><b>For use with:</b> 4-liter blender bases only</p>

	Part Number / Description
	<p><b>CAC170</b> 4-liter (stackable) copolyester container</p> <p><b>For use with:</b> 4-liter blender bases only</p>
	<p><b>CBL10</b> Hot blending lid for 4-liter blenders</p> <p><b>For use with:</b> CAC70, CAC72, 2610C</p>
	<p><b>AD1</b> Adapter for 4-liter blenders. Allows the use of 1.2-liter and smaller containers</p> <p><b>For use with:</b> 4-liter blender bases</p>


# LABORATORY ACCESSORIES





## For use with HGB Series Blenders.

	Part Number / Description
	<p><b>CAC15</b> Hot blending lid for 2-liter units</p> <p><b>For use with:</b> 2-liter stainless steel containers</p>
	<p><b>CAC21</b> 1.5-liter, BPA-free, copolyester container with two-piece lid</p> <p><b>For use with:</b> 2-liter blender bases only</p>
	<p><b>CAC59</b> 2-liter, BPA-free, copolyester container with two-piece lid</p> <p><b>For use with:</b> 2-liter blender bases only</p>

	Part Number / Description
	<p><b>SS715</b> 1-liter stainless steel container with two-piece lid</p> <p><b>For use with:</b> 2-liter blender bases only</p>
	<p><b>AD2</b> Adapter for 2-liter blender bases. Allows the use of 1.2-liter and smaller containers</p> <p><b>For use with:</b> 2-liter series blender bases.</p>


## For use with Immersion Blenders.


	Part Number / Description
	<p><b>WSB50ST</b> 30.5 cm/12" shaft</p> <p><b>For use with:</b> All heavy-duty immersion blenders</p>
	<p><b>WSB55ST</b> 35.6 cm/14" shaft</p> <p><b>For use with:</b> All heavy-duty immersion blenders</p>
	<p><b>WSB60ST</b> 40.6 cm/16" shaft</p> <p><b>For use with:</b> All heavy-duty immersion blenders</p>
	<p><b>WSB65ST</b> 45.7 cm/18" shaft</p> <p><b>For use with:</b> All heavy-duty immersion blenders</p>
	<p><b>WSB70ST</b> 53.4 cm/21" shaft</p> <p><b>For use with:</b> All heavy-duty immersion blenders</p>

	Part Number / Description
	<p><b>WSBBC</b> Bowl clamp</p> <p><b>For use with:</b> All heavy-duty immersion blenders</p>
	<p><b>WSB01</b> Wall-mount bracket</p> <p><b>For use with:</b> WSB40 series and all heavy-duty immersion blenders</p>
	<p><b>WSB2W</b> 10" stainless steel whisk attachment</p> <p><b>For use with:</b> All heavy-duty immersion blenders</p>
	<p><b>WSBPP</b> – Power pack, 120V ☺ <b>WSBPPCE</b> – Power pack, 230V ☺ <b>WSBPPCK</b> – Power pack, 230V ☺</p> <p><b>For use with:</b> WSB50ST WSB60ST WSB65ST WSB70ST WSB2W</p>







# LABORATORY ACCESSORIES


## For use with Grinders and Pulverizers.

	Part Number / Description
	<b>CAC103</b> Grinding bowl with lid <b>For use with:</b> WSG30 grinder/pulverizer

	Part Number / Description
	<b>CAC128</b> Grinding bowl with lid <b>For use with:</b> WSG60 grinder/pulverizer

## For use with Planetary Mixers.

	Part Number / Description
	<b>WSM7LMP</b> Mixing Paddle for WSM7
	<b>WSM10LMP</b> Mixing Paddle for WSM10
	<b>WSM20LMP</b> Mixing Paddle for WSM20
	<b>WSM7LW</b> Whisk for WSM7
	<b>WSM10LW</b> Whisk for WSM10
	<b>WSM20LW</b> Whisk for WSM20

	Part Number / Description
	<b>WSM7LDH</b> Hook for WSM7
	<b>WSM10LDH</b> Hook for WSM10
	<b>WSM20LDH</b> Hook for WSM20
	<b>WSM7LBL</b> Stainless Steel Bowl for WSM7
	<b>WSM10LBL</b> Stainless Steel Bowl for WSM10
	<b>WSM20LBL</b> Stainless Steel Bowl for WSM20



#### PT MULTI FLASHINDO KARISMA

##### □ JAKARTA *(Head Office)*

Jl. Hayam Wuruk 114 Blok A No. 4  
Maphar, Jakarta - Indonesia 11160  
Telepon : +62 21 626 8758  
Whatsapp : +62 811 1210 6803  
Email : sales.dept@mfk.co.id

##### □ SURABAYA

Ruko Royal Crown Palace RA 2  
Jl. H. Anwar Hamzah, Kp. Baru, Tambakoso,  
Kec. Waru, Kab. Sidoarjo, Jawa Timur 61256  
Telepon : +62 31 3592 9091  
Whatsapp : +62 811 1210 6803  
Email : sales.sby@mfk.co.id

##### □ BALI

Jl. Sunset Road No.108 B, Kec. Kuta  
Kel. Badung, Bali - Indonesia 80361  
Telepon : +62 361 934 2633  
Whatsapp : +62 811 1210 6803  
Email : sales.bali@mfk.co.id

##### □ SERVICE CENTER

Jl. Kamal Raya No.9 Unit B. RT 01/ RW 06  
Tegal Alur. Cengkareng - Indonesia 11820  
Telepon : +62 21 5595 2523  
Whatsapp : +62 811 9144 614  
Email : service.center@mfk.co.id